

245

68

295

60

130

100

1730

41

mm

mm

mm


mm

mm

mm

mm

mm



STAGE	1	2	3	4	5	6	7	8	TOTAL
EFFECTIVE DIAMETER (mm)	Ø 212	Ø185	Ø160	Ø135	Ø116				
STROKE	1400	1400	1400	1400	1400				7000
OIL DISPLACEMENT (L)									210
THRUST AT 160 BAR (TONS)	45	34	24	18	12,5				

BL		7300			7100			6900	
Ro	200	500	800	200	500	800	200	500	800
α°	45	47	50	46	49	51	48	50	53
Ycog									
600	39	42	48	40	44	49	41	45	51
900	42	47	53	43	49	56	45	51	59
1200	46	52	60	48	55	65	50	58	70
st	5475	5483	5583	5443	5553	5525	5520	5500	5565

- * The Cylinder has only the function of lifting and the equipment and shoud not be used for this.
- * Working pressure depends on the application
- * Never exceed the max. working pressure stated.
- * Hard Chromed all stages

NOTICE:

- * 'Büyükyüksel Damper Hid. Mak. San. Tic. Ltd. Şti.' has adopted principle of continuous improvement its products
- * 'Büyükyüksel Damper' reserves the right to make changes in technical dimensions and features without prior notice
- * So; this technical drawing is given to be added to the contract annex and it is for only informational purposes

	Name	Date & Signature				
Designer	A.TAŞDELEN		BÜYÜKYÜKSEL			
Control	A.ADIYAMAN		DAMPER HİD. MAK. SAN. TİC. LTD. ŞTİ.			
Approval	O.ADIYAMAN		Trademark Name: SEMITÜRK			
Type Approval	e5*2018/858*00075	5*00	www.yukseldamper.com.tr			
Q.M.S. / No.	ISO 9001:2015 / QA	NS-0104558	www.semiturk.com.tr			
Product Code	TX-SA-H5SC-45 (212	2-5-7000 C)	info@yukseldamper.com.tr			
Product Name	5 Stage Hydraulic	Cylinder for Tipper	+90 530 610 1432 / +90 332 239 1860			
Type Approval Q.M.S. / No. Product Code	e5*2018/858*00075 ISO 9001:2015 / QN TX-SA-H5SC-45 (212	AS-0104558 2-5-7000 C)	www.yukseldamper.com.tr www.semiturk.com.tr			

All rights of this picture belong to BÜYÜKYÜKSEL DAMPER LTD. STI. So, it can not be reproduced, copied and published without permission

2 3 5