

Body / Chassis:

Manufactured from high-strength sheet metal by using gas metal arc welding machines. Chassis and frame structure are suitable for heavy-loads and designed as durability.

- Front wall is 2 mm 'S235JR or equivalent'
- Side walls is 2 mm 'S235JR or equivalent'
- Rear wall is 3 mm 'S235JR or equivalent'
- Base floor is 3 mm 'S235JR or equivalent'
- Inner frame structure profiles 80x80 mm
- Outer frame main support profiles 100x100 mm

* Since will be installed on the prime mover (truck) or trailer chassis; additional sub chassis is not supplied by seller in the standard combination

* Unless otherwise specified in the contract, installation of equipment on prime mover (any type truck, semi-trailer or trailer) will be done by buyer

Hydraulic System:

- 2 hydraulic cylinders for each basket
 - * **Optional** 2-stage tipping mechanism with 4 hydraulic cylinders for each basket
- 1 piece 22-cc hydraulic flow divider valve per basket (for tipping mechanism with 2 cylinders)
- Single arm, hydraulic directional control valve (mono block hydraulic control lever)
- Hydraulic fitting, hydraulic hoses and connecting attachments (for only basket/s)

Documentation:

- Operation instruction / guide for use
- Maintenance instruction / guide
- Installation instruction / guide
- Fast and slow moving spare parts list

Optional Features:

- 6 - 8 - 10 tons load capacity options
- Additional sub chassis options compatible with main chassis of prime mover
- Completion of equipment installation by the seller (provided that the prime mover (any type truck, semi-trailer or trailer) is directed to the production area);
 - * Equipment installation to prime mover chassis
 - * Supply and mounting of PTO (or any external hydraulic drive unit)
 - * Supply and mounting of piston or gear type hydraulic pump
 - * Supply and mounting of hydraulic oil tank
 - * Prime mover - equipment hydraulic line installation (hydraulic hoses, hydraulic fitting and connecting attachments)
- 24 Volt lighting hardware with electrical socket
 - * Side yellow lighting lamps, rear and front white lighting lamps, rotary lamp
- Engineer-supported overseas maintenance / repair / usage training for users
- Standard tool kits in locking type tool boxes

Date: 14.11.2023

Dimensions and Weight:

Length of Each 1 Basket	: 3.580 mm
Total Length of 2 Basket	: 7.380 mm
Total Width	: 2.962 mm
Total Height	: 3.123 mm
Unloading Height from Chassis	: 3.210 mm
Each 1 Basket Max. Load Cap.	: 6.000 kg
Each 1 Basket Usable Volume	: 15,3 m ³
Each 1 Basket Tare Weight	: 3.150 kg
Without Sub Chassis (±%5)	

* All dimensions can modify with design options

* Technical drawing is submitted with the offer

* Manufacturer reserves the right to make changes in technical dimensions and features without prior notice

* "The buyer & beneficiary" accepts and undertakes that he/she is responsible for any problems that may arise due to non-compliance with national and/or international traffic regulations regarding dimensions and specifications

Painting: Metal parts are painted with 2-layers anti-corrosive epoxy primer then top acrylic paint coat with up-to-date RAL colour

Standard Accessories:

- Yellow and red warning reflectors
- Standard truck reflector
- Chassis mounting brackets

Warranty: Our products are under 1 year warranty against manufacturing defects

* 5-year spare parts supply warranty



Unit Price (EXW & Konya / TURKEY):

- Euro / Each 1 Unit - EXW delivery
- * Export or export registered invoice price
- * Price is valid for 7 days from the date of offer
- * Optional features provide with extra charge

Payment Terms:

- %60 prepayment, %40 in advance of delivery

Delivery: 25 working days / up to 5 units

- * Delivery time is variable with order date
- * Our company 'ISO 9001:2015 QMS' certified
- * Delays and incompatibilities arising from force majeure are not taken into account